



BAKER F 550 CCG L2 25B

Product series: Baker

Item number: 965500201



The GRAM BAKER F 550 CCG L2 25B is with a net internal volume of 314 Ltr.

Generations of bakeries, confectioners, and patisseries are trusting GRAM BAKER storage and process cabinets to accommodate their bakery products. The GRAM air circulation system is key to maintain correct and uniform temperatures inside the cabinet. The air is exhausted and refrigerated before being directed back into the cabinet, circulating around all food items. Thus, unwanted dehydration and skin forming of doughs can be avoided almost entirely.

Preserving Quality

Both storage and process cabinets come with built-in functionalities that preserve the quality of your bakery products at all times.

Low Running Costs

The energy-efficient refrigeration technology implemented in this wide line-up of storage cabinets can help saving running costs on a day-to-day basis.

Built-in Safety

All BAKER Cabinets come with a controller equipped with safety functions: Door alarm, alarms for high-temperature levels, or when the cleaning of the condenser filter is required to avoid overheating. A top panel perfectly protects the controller from water splashes.

Designed for Bakers

The GRAM BAKER series strikes with features, specifically designed for the requirements of bakery businesses. The cabinet meets standard bakery tray sizes and the support rails can be individually positioned.

The BAKER F 550 CCG L2 25B comes with the following extras:

Right-hand hinged door with lock

Air circulation system

Dry cooling and controlled thawing (M versions)

Automatic defrost and reevaporation of water

SPECIFICATIONS

| | | | |
|-------------------------------|-------------------|-------------------------------|---|
| Temperature range | -25/-5°C | Power supply | 230V, 50 Hz |
| Volume, gross (ltr.) | 465 | Connection load (Watt) | 418 |
| Net usable volume (ltr.) | 314 | Energy consumption (kWh/Year) | 1.355 |
| Exterior | Stainless | Energy efficiency class | C |
| Interior | Stainless | Climate class | 5 |
| Dimensions W x D x H (mm) | 600 x 855 x 2125 | Legs / Castors | H = 135/200 mm (L2) |
| Weight, packed (kg) | 132 | Refrigerant (kg) | 0,145 |
| Insulation (mm) | 70 (cyclopentane) | CO2 equivalent (kg) | 0,435 |
| Refrigerant | R290 | GN or Shelf size | Trayslides 600 x 400 mm |
| GWP | 3 | Equipped with | Right hand hinged reversible door with lock, automatic door closing; Pedal door opener with overload protection; 25 pairs of adjustable supports (40x60 cm) |
| Ref. capacity at -25°C (Watt) | 499 | Door Type | Insulated Door |