

Modular Cooking Range Line EVO700 4-Hot Plates Electric Boiling Top Range

ITEM #	
MODEL #	
NAME #	
SIS#	
AIA #	



Main Features

- Unit to be mounted on open base cupboards, bridging supports or cantilever systems.
- The four 2.6kW cast-iron plates are hermetically sealed to the one-piece top.
- The special design of the control knob system guarantees against water infiltration.
- IPx4 water protection.
- Suitable for countertop installation.

Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

372015 (Z7ECEH4R00)

4-hot plate (2,6 kW each) electric boiling top

372127 (Z7ECEH4R0N)

4-hot plate (2,6 kW each) electric boiling top

Short Form Specification

Item No.

To be installed on open base installations, bridging supports or cantilever systems. Four 2.6 kW cast-iron hot plates hermetically sealed to the one-piece top. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

APPROVAL:



Modular Cooking Range Line EVO700 4-Hot Plates Electric **Boiling Top Range**

Optional Accessories

-		
 Junction sealing kit 	PNC 206086	
 Support for bridge type installation, 800 mm 	PNC 206137	
 Support for bridge type installation, 1000 mm 	PNC 206138	
 Support for bridge type installation, 1200 mm 	PNC 206139	
 Support for bridge type installation, 1400 mm 	PNC 206140	
 Support for bridge type installation, 1600 mm 	PNC 206141	
Frontal handrail 800 mm	PNC 206167	
 Large handrail (portioning shelf) 800 mm 	PNC 206186	
 Frontal handrail 1200 mm 	PNC 206191	
 Frontal handrail 1600 mm 	PNC 206192	
 Right and left side handrails 	PNC 206240	
 Water column with swivel arm (water column extension not included) 	PNC 206289	
 Water column extension 	PNC 206291	
 Chimney upstand, 800 mm 	PNC 206304	
• 2 side covering panels, height 250 mm, depth 700 mm	PNC 206320	
Chimney grid net, 400mm	PNC 206400	















Modular Cooking Range Line EVO700 4-Hot Plates Electric Boiling Top Range

Front 31 1/2 " 800 mm 13 1/16 332 п E Q \bigcirc ΕI 3 15/16 " 100 mm 2 1/16 " 52 mm 0 7/16 " 30 5/8 " 0 7/16 " 11 mm 778 mm 11 mm



EI = Electrical inlet (power) Equipotential screw =



Electric

Supply voltage:

372015 (Z7ECEH4R00) 380-400 V/3 ph/50/60 Hz 372127 (Z7ECEH4RON) 230 V/3 ph/50/60 Hz

Total Watts: 10.4 kW

Predisposed for:

380-400V 3~ 50/60Hz

372015 (Z7ECEH4R00) 9-10,4kW

Key Information:

Front Plates Power: 2.6 - 2.6 kW **Back Plates Power:** 2.6 - 2.6 kW Front Plates dimensions: Ø 230 Ø 230 **Back Plates dimensions:** Ø 230 Ø 230 Net weight: 40 kg Shipping weight: 38 ka Shipping height: 372015 (Z7ECEH4R00) 530 mm 372127 (Z7ECEH4RON) 540 mm Shipping width: 820 mm

Shipping depth: Shipping volume:

> 372015 (Z7ECEH4R00) 0.37 m³ 372127 (Z7ECEH4RON) 0.38 m³

Certification group:

372015 (Z7ECEH4R00) EH74T 372127 (Z7ECEH4RON) N7CE1

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

860 mm











Modular Cooking Range Line EVO700 4-Hot Plates Electric Boiling Top Range